

SILENCED

SUPPRESSOR AND MUZZLE BRAKE CLEANER



PRODUCT DESCRIPTION

SILENCED is a chemical compound developed to deep-clean rifle and sidearm suppressors and muzzle brakes. SILENCED is specially engineered to lift carbon and other residues from metal surfaces and keep it in suspension while the special chemical surfactant blend goes to work on the rinsing and neutralising of residual fouling.

Our technology enables the cleaner to penetrate small spaces and crevices to remove fouling and loosen stubborn deposits that hamper equipment functionality. SILENCED is safe for use on various metal and coated surfaces but anodized surfaces should be avoided. SILENCED was developed to silence your problem without cleaning out your pocket

500 ml | VLD - SLD500

RECOMMENDED DIRECTIONS

- Secure and unload the firearm.
- Remove the suppressor or muzzle brake.

REACTION:

- Make use of an appropriate rubber plug to plug the suppressor tip and fill it with SILENCED.
- Disassembled suppressors, muzzles and equipment can be submerged in the cleaner.
- Expose your equipment to SILENCED for 2-4 hours.
- For excessively fouled suppressors and muzzle brakes, you can leave the cleaner in contact for an extended time (min 6 hours).
- The cleaner can be heated to a max of 40C to elevate reaction time.
- Stubborn dirt might require light, non-abrasive scrubbing for optimal results.
- Remove liquid from the suppressor and reclaim the cleaner for another future cycle.

REMOVING RESIDUE:

- Fill the silencer halfway with clean water and shake.
- Rinse repeatedly until no residue is visible in the drained water.
- Disassembled parts can be wiped clean using a cloth or paper towel to remove all carbon deposits that are present on the equipment. Ensure that equipment is completely and properly dried.

NOTE:

Polymer, plastic, and anodized parts should only be subjected to ultrasonic cleaning, using this solvent, for 3-5 minutes at a time. Check coatings to ensure safety throughout use. Ultrasonic tanks must be thoroughly cleaned before the tank was used for case cleaning prior to use on parts. This will avoid brass particle coating from adhering to equipment surfaces.

RECOMMENDED

REMOVAL OF SOOT,
CARBON AND RESIDUE

COMPATIBILITY

SUPPRESSORS
MUZZLE BRAKES
FORGING CONES

LEGAL DISCLAIMER

Neither VELDT MARKSMAN nor the seller is responsible for how the user applies, handles or manipulates this product.

Neither VELDT MARKSMAN nor the seller is liable for warranties lost or implied nor any direct or indirect damage and injuries sustained, that might occur as a result of product misuse or acts conducted by the user. The user must read and keep to the directions supplied.

Please read the technical data sheet on our website: www.veldtsa.com

Not for human or animal consumption.

Always test the product on barrels and coatings before application.

Keep out of reach of children.

Store in a cool, dry place away from direct sunlight.



MAKE USE OF
GLOVES



USE EYE
PROTECTION



HARMFUL IF
SWALLOWED



BIODEGRADABLE
INGREDIENTS

SPECIAL ABILITY

SILENCED is engineered to clean three silencers making use of the same liquid. (The amount of cleaning cycles for the liquid depends on the cleaning frequency and the extent of the fouling on your equipment. If the liquid is spent replace it with a fresh batch.)

Engineered to suspend solids found in silencers. SILENCED has a penetrating characteristic that helps loosen tight threads.

Superior cleaning ability with precision chemical technology for the precision enthusiast.



IMPORTANT NOTES

CERAKOTE SAFE

- Do not fire a round with the product inside the silencer. Make sure that the silencer is dry before use.
- Not suitable for anodized surfaces when exposed for indefinite time periods.
- Do not leave equipment exposed for infinite amount of time without supervision.